

Solar AGM Battery 12V12ah

Basic Info

- Model NO.: 6FM12
- Usage: UPS, Electric Power, Lighting
- Discharge Rate: Low Discharge Rate
- Electrolyte: Acid
- Rechargeable: Chargeable
- Voltage: 12V
- Approx Dimension(mm): 151*98*95
- Terminal: T2
- Specification: CE, SGS
- HS Code: 850720000
- Type: Lead-Acid Batteries
- Nominal Voltage: 12V
- Shape: Square Battery
- Installation: Fixed
- Model No.: 6FM12
- Capacity: 12ah/20hr
- Total Weight: 3.5kg
- Trademark: TIGER HEAD
- Origin: Guangzhou, China

Product Description



- **VRLA-AGM BATTERY**
Guangzhou Tiger head Vrla-AGM Batteries indicate Valve-Regulated Lead-Acid batteries with Absorbed Glass Mat(AGM)separators. By using the matured technology invented more than half century.now we are able to design,build and market high quality,long life VRLA-AGM batteries from 2V to 24V,and 0.5AH to 3500AH.Tiger Head is now one of the fastest developing lead-acid battery manufactures in China

General Purpose Applications:
ALL Purpose battery Needs

•

UPS	EPS	Emergency Light	Signal	Security System
Electronic Equipment	DC Power Supply	Tele-Communication	Power System	Network Communication

•

Deep Cycle Application:

Electric Tools	Lawn Mowers	Golf Trolleys	Portable Apparatus
Electric Toys	Illumination Light	Wheel Chairs	Medical Equipments

- **Solar/Wind/Hydro Power System Applications:**

Green Energy Systems	Measurement Stations	Pump System	Signal Station	Emergency Lighting	Railway Crossing	Traffic Lights
Street Lighting	Lawn Lamp	SOS Pillars	Camping	Boats or Buoys	Communication System	

- Long life Standby Application:

UPS	EPS	Emergency Light	Railway Signal	Electronic Apparatus
Communication DC Power	Tele-Communication	Power System Communication	Network Communication	Marine

- High Rate Discharging/UPS Applications:

UPS(High rate)	High Power Backup	Starting System
Power Tools	Emergency Lighting	Electric Starting

- Front Terminal/Telecom Applications:

For Standard 19 Inch or 23 Inch Power Cabinets	Network Connection Equipment	UPS
Power Station Systems	Railway and Marine Systems	

-

FEATURES

- .Maintenance-free, no water adding required
- .Sealed Valve-Regulated
- .Spill proof/leak proof
- .Deep discharge protection
- .Plate grids from lead-calcium alloy, free of antimony
- .No corrosion
- .Installs vertically or horizontally
- .Low gassing(unless overcharged)
- .Good cycling and stationary performance
- .Long shelf life
- .Rugged and vibration-resistant